



US 20040075381A1

(19) **United States**

(12) **Patent Application Publication**  
Burroughes et al.

(10) **Pub. No.: US 2004/0075381 A1**  
(43) **Pub. Date: Apr. 22, 2004**

(54) **ELECTROLUMINESCENT DEVICES**

(75) Inventors: **Jeremy Henley Burroughes, Cambridge (GB); Richard Henry Friend, Cambridge (GB); Christopher John Bright, Huntingdon Cambridgeshire (GB); David John Lacey, Hertfordshire (GB); Peter Devine, Cambridge (GB)**

Correspondence Address:  
**FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER LLP**  
**1300 I STREET, NW**  
**WASHINGTON, DC 20005 (US)**

(73) Assignee: **Cambridge Display Technology Limited**

(21) Appl. No.: **10/682,204**

(22) Filed: **Oct. 10, 2003**

**Related U.S. Application Data**

(63) Continuation of application No. 09/508,367, filed on Jan. 3, 2002, filed as 371 of international application No. PCT/GB99/00741, filed on Mar. 12, 1999.

**(30) Foreign Application Priority Data**

Mar. 18, 1998 (GB) ..... 9805476.0

**Publication Classification**

(51) **Int. Cl. 7** ..... H01J 1/62; H01J 63/04;  
H01L 21/00  
(52) **U.S. Cl.** ..... 313/504; 313/483; 438/99;  
438/22

**(57) ABSTRACT**

An electroluminescent device comprising: a first charge carrier injecting layer for injecting positive charge carriers; a second charge carrier injecting layer for injecting negative charge carriers; and a light-emissive layer located between the charge carrier injecting layers and comprising a mixture of: a first component for accepting positive charge carriers from the first charge carrier injecting layer; a second component for accepting negative charge carriers from the second charge carrier injecting layer; and a third, organic light-emissive component for generating light as a result of combination of charge carriers from the first and second components; at least one of the first, second and third components forming a type II semiconductor interface with another of the first, second and third components.

